


S-TRACK 3-phase surface-mounted track

240V track, white, 2 m

Aluminium bearing track of the 240V 3-circuit surface-mounted track system. Installation can take place through the existing holes in the profile directly onto the wall or the ceiling. The surface-mounted version of this system is available in several colours and lengths. Alternatively, there is a recessed version available too. Please note that the white colour will be changing from RAL 9010 to RAL 9016 (traffic white) on 1st October 2018. More information can be found under Product Information in the ?Service? / Downloads area.



TECHNICAL DATA

Item no.:	175021
Nominal voltage	220-250V ~50Hz V
Length	199.5 cm
Width	3.6 cm
Height	3.6 cm
Net weight	1.775 kg
Gross weight	2.212 kg
IP Code	IP 20
Safety class	
Assembly	Surface
Assembly details	Ceiling, Wall
Color	white

							4				4			4		ч		ч	ч	ч	ч	ч	J	4	4	4	4								
	4	- 4		ı	a,	J,	J.	J	4	a	J	J	J	J	ä	a	ä	ä	J.																
١.	ı .	LL	1	1	ı	ı	J	J.	J	4	J	J	J	J	J	J	J		1			ı		1		1	ı	1	ı	J.	a,	١,	1	1	1
					ı			á		ā		J	ä	J	ä	ä	J	J	J.	J	J.	1	J.	. د	1	J	J.	ă,							



Notes			