





STRUCTEC

spot for 240V 3-phase tracks, LED, 3000K, round, white, 36°, 30W, incl. 3-phase adapter

The STRUCTEC is available in several colour versions and beam angles with a suitable adapter for the 3-phase 240V track system. It has a high-performance COB LED module fitted, which, thanks to a CRI of >90, is especially suitable for excellent colour reproduction.





TECHNICAL DATA

| Item no.: | 176081 | | |
|-------------------------------------|------------------------|--|--|
| Lamps included | 0 | | |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V | | |
| Secondary power / secondary voltage | 900 mA/V | | |
| Vertical tilting range | 85 ° | | |
| Horizontal rotation range | 350 ° | | |
| Length | 16.8 cm | | |
| Height | 16.5 cm | | |
| Diameter | 9.0 cm | | |
| Net weight | 1.117 kg | | |
| Gross weight | 1.359 kg | | |
| IP Code | IP 20 | | |
| Safety class | I | | |
| Assembly | Surface | | |
| Assembly details | Track Ceiling | | |
| Wattage | 35.0 W | | |
| Lumen | 2600 lm | | |
| Colour temperature | 3000 Kelvin | | |
| Beam angle | 36 ° | | |
| Color | white | | |
| CRI | >96 | | |
| Binning | 3 | | |





| LXXBXX data | 70/50 |
|----------------|---------|
| Service life | 40000 h |
| BIG WHITE Page | 356 |

| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |