



DASAR FLAT 80

outdoor inground fitting, LED, 3000K, IP67, round, brushed stainless steel, $4.3\mathrm{W}$

The 240V inground fitting DASAR FLAT 80 has a round stainless steel shade and frosted glass cover and is fitted with a high-performance power LED module. With protection class IP67, the luminaire available in two colours of light is suitable for outdoor use. The electrical connection is made using the connection lead included directly to the 230V mains supply. A mounting pot is included in the delivery for simple assembly.

TECHNICAL DATA

Item no.:	228412		
Lamps included	0		
Primary nominal voltage	230V ~50/60Hz mA/V		
Height	5.8 cm		
Diameter	8.0 cm		
Installation diameter	8.8 cm		
Installation depth	5.7 cm		
Net weight	0.417 kg		
Gross weight	0.477 kg		
IP Code	IP 67		
Safety class	I		
Impact resistance class	IK08		
Impact resistance	5 Joule		
Assembly	Recessed		
Assembly details	Ground,Wall		
Wattage	4.3 W		
Lumen	140 lm		
Colour temperature	3000 Kelvin		
Beam angle	125 °		
Color	stainless steel		
CRI	>80		
LXXBXX data	70/50		





Service life	30000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Mechanical loading	0,18 t
BIG WHITE Page	722

Notes			