



## DASAR 80

**outdoor inground fitting, QR-CBC51, IP67, tiltable, square, stainless steel 316, max. 35W**

The walkable low-voltage inground fitting with square stainless steel shade and partially frosted glass cover is equipped with a GU5.3 socket and is thus compatible with halogen and LED lamps. With its IP67 protection class, the luminaire is suitable for outdoor use. The electrical connection is made via a separately available low-voltage transformer providing 12V. A mounting pot is included in the delivery for simple assembly.

## TECHNICAL DATA

Item no.:	229334
Socket	GU5.3
Lamp	QR-CBC51
Number of sockets	1
Lamps included	0
Primary nominal voltage	12V ~50/60Hz mA/V
Tilt range	30 °
Horizontal rotation range	90 °
Length	13.0 cm
Width	13.0 cm
Depth	16.0 cm
Installation diameter	11.5 cm
Installation depth	16.5 cm
Net weight	1.053 kg
Gross weight	1.207 kg
IP Code	IP 67
Safety class	III
Impact resistance class	IK08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground
Wattage	35.0 W

## Recommended lamp

1001574	Philips Master LED Spot MR16 , 5W, 2700K, 36°, dimmable
1001575	Philips Master LED MR16 5W , 3000K, 36°

Color	stainless steel
Mechanical loading	2 t

## Accessories

227150	TRANSFORMER , 150VA, 12V, IP44
227160	TRANSFORMER , 60VA, 12V, IP44

227150	TRANSFORMER , 150VA, 12V, IP44
227160	TRANSFORMER , 60VA, 12V, IP44

## Notes

---

---

---

---