



DASAR 115

outdoor inground fitting, QR-CBC51, IP67, rigid, square, stainless steel 316, max. 35W

The walkable low-voltage inground fitting with square stainless steel shade and partially frosted glass cover is equipped with a G5.3 socket and is thus compatible with halogen and LED lamps. With its IP67 protection class, the luminaire is suitable for outdoor use. The electrical connection is made via a separately available low-voltage transformer providing 12V. A mounting pot is included in the delivery for simple assembly.

TECHNICAL DATA

| | |
|-------------------------|-----------------|
| Item no.: | 229344 |
| Socket | GX5.3 |
| Lamp | QR-CBC51 |
| Number of sockets | 1 |
| Lamps included | 0 |
| Primary nominal voltage | 12V ~50Hz mA/V |
| Height | 13.0 cm |
| Installation diameter | 10.1 cm |
| Net weight | 0.83 kg |
| Gross weight | 1.027 kg |
| IP Code | IP 67 |
| Safety class | III |
| Impact resistance class | IK08 |
| Impact resistance | 5 Joule |
| Assembly | Recessed |
| Assembly details | Ground |
| Wattage | 35.0 W |
| Color | stainless steel |
| Mechanical loading | 20 t |

Recommended lamp

| | |
|---------|--|
| 1001574 | Philips Master LED Spot MR16 , 5W, 2700K, 36° , dimmable |
| 1001575 | Philips Master LED MR16 5W , 3000K, 36° |

Accessories

| | |
|--------|--------------------------------|
| 227150 | TRANSFORMER , 150VA, 12V, IP44 |
| 227160 | TRANSFORMER , 60VA, 12V, IP44 |

Notes
