



ROX PATHLIGHT

outdoor floor stand, QPAR111, IP44, brushed aluminium, max. 50W

The aluminium-made floor stand ROX PATH LIGHT consists of a square housing and a round, tiltable lamp head. We offer one version for 240V halogen or LED lamps with GU10 socket and another version for energy-saving or LED lamps with GX53 socket. With protection class IP44, it is suitable for outdoor use. For simplified mounting, through-wiring is possible and an earth-spike and a concrete anchor set are available as accessories.

TECHNICAL DATA

| | |
|-------------------------|--------------------------|
| Item no.: | 229836 |
| Socket | GU10 |
| Lamp | QPAR111 |
| Number of sockets | 1 |
| Lamps included | 0 |
| Primary nominal voltage | 230V ~50Hz mA/V |
| Tilt range | 180 ° |
| Length | 21.5 cm |
| Width | 12.5 cm |
| Height | 61.0 cm |
| Net weight | 2.858 kg |
| Gross weight | 3.438 kg |
| IP Code | IP 44 |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ground, Ground with Acc. |
| Wattage | 50.0 W |
| Color | aluminium |

Recommended lamp

| | |
|--------|--|
| 551642 | LED ES111 , CREE XB-D LED, grey, 17W, 30°, 2700K, dimmable |
|--------|--|

Accessories

| | |
|--------|--|
| 228726 | T-CONNECTIONBOX , black, IP68 |
| 229840 | CONCRETE ANCHOR for ROX PATH-LIGHT |
| 229841 | EARTH SPIKE , for ROX PATHLIGHT and DELWA PATHLIGHT 60 |

Notes
