




FLOOD LIGHT

outdoor façade light, LED, 5700K IP65, matt black, 90° , 82.3W

Powerful FLOOD LIGHT spot for illuminating areas and spaces. With a tiltable installation bracket and protection class IP65, the spot is suitable for outdoor installation on the wall, ceiling or on the floor. The electrical connection of the spot, which is available in warm white and neutral white, is made directly by the built-in driver and the connection lead with mains plug to the 230V mains supply. An earth spike is available as an option for simplified floor installation.



TECHNICAL DATA

Item no.:	231175		
Lamps included	0		
Primary nominal voltage	220-240V ~50Hz mA/V		
Vertical tilting range	180 °		
Length	39.0 cm		
Width	12.5 cm		
Height	46.5 cm		
Net weight	6.775 kg		
Gross weight	7.415 kg		
IP Code	IP 65		
Safety class	I		
Assembly	Surface		
Assembly details	Ceiling,Ground,Wall		
Wattage	82.3 W		
Lumen	7950 lm		
Colour temperature	5700 Kelvin		
Beam angle	90 °		
Color	black		
CRI	>70		
Binning	6		
LXXBXX data	70/50		
Service life 30000 h			





Ambient temperature	40 °C

Accessories

234340	Wall bracket , for Outdoor Beam and MILOX floodlight, black, 50cm
234350	WALL BRACKET , for SPOODI 15/20/31, black, 80 cm

Notes		