




BENDO

outdoor floor stand, LED, 3000K, IP55, anthracite, L/- W/H 35/21/80 cm, 12W $\,$

The angled aluminium BENDO floor stand is fitted with a large number of powerful LEDs. With protection class IP55, it is suitable for outdoor use. Available in three sizes, it is supplied with open cable ends for simple installation. A concrete anchor, connection box and T-connection box are available as an option. This luminaire contains built-in LED lamps. The LED cannot be changed in the luminaire.



TECHNICAL DATA

Item no.:	231835		
Lamps included	0		
Number of different light outlets	1		
Primary nominal voltage	220-240V ~50/60Hz mA/V		
Length	35.0 cm		
Width	21.0 cm		
Height	80.0 cm		
Net weight	3.261 kg		
Gross weight	5.238 kg		
IP Code	IP 55		
Safety class	I		
Impact resistance class	IK06		
Impact resistance	1 Joule		
Assembly	Surface		
Assembly details	Ground, Ground with Acc.		
Wattage	11.0 W		
Lumen	700 lm		
Colour temperature	3000 Kelvin		
Beam angle	80 °		
Color	anthracite		
CRI	>80		
Binning	6		



Accessories

228726	T-CONNECTIONBOX , black, IP68
228730	CONNECTION BOX , 3-pin, IP68
231849	CONCRETE ANCHOR , for BENDO outdoor floor stand, silver

LXXBXX data	70/50
Service life	35000 h
Minimum ambient temperature	-25 °C
Maximum ambient temperature	50 °C
BIG WHITE Page	572

Notes		