


BENDO

outdoor floor stand, LED, 3000K, IP55, anthracite, L/-
W/H 47.5/21/225 cm, 12W

The angled aluminium BENDO floor stand is fitted with a large number of powerful LEDs. With protection class IP55, it is suitable for outdoor use. Available in three sizes, it is supplied with open cable ends for simple installation. A concrete anchor, connection box and T-connection box are available as an option. This luminaire contains built-in LED lamps. The LED cannot be changed in the luminaire.

TECHNICAL DATA

Item no.:	231845
Lamps included	0
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Length	47.5 cm
Width	21.0 cm
Height	225.0 cm
Net weight	7.071 kg
Gross weight	10.135 kg
IP Code	IP 55
Safety class	I
Impact resistance class	IK06
Impact resistance	1 Joule
Assembly	Surface
Assembly details	Ground,Ground with Acc.
Wattage	31.0 W
Lumen	1800 lm
Colour temperature	3000 Kelvin
Beam angle	80 °
Color	anthracite
CRI	>80
Binning	6



Accessories

228726	T-CONNECTIONBOX , black, IP68
228730	CONNECTION BOX , 3-pin, IP68
231849	CONCRETE ANCHOR , for BENDO outdoor floor stand, silver

LXXBXX data	70/50
Service life	35000 h
Minimum ambient temperature	-25 °C
Maximum ambient temperature	32 °C
BIG WHITE Page	572

Notes