



H-POL

pathway and floor stand, double-headed, LED, 3000K, anthracite, L/W/H 16.5/16.5/66 cm

The H-POL DOUBLE indirect radiating floor stand is made of aluminium and plastic. With protection class IP55, it is suitable for outdoor use. Thanks to the two 8W LEDs, the luminaire is ideal for use as a pathway light. The product is designed for floor installation and is through-wireable. A large mounting pot is available for optimum mounting in the earth. Thanks to the built-in LED driver, it can be connected directly to the 230V mains supply.

TECHNICAL DATA

Item no.:	232185
Lamps included	0
Number of different light outlets	2
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	1000 mA/V
Length	16.5 cm
Width	16.5 cm
Height	66.0 cm
Installation length	11.8 cm
Installation width	11.8 cm
Installation depth	10.0 cm
Net weight	2.602 kg
Gross weight	3.427 kg
IP Code	IP 55
Safety class	I
Assembly	Recessed
Assembly details	Ground, Ground with Acc.
Number of through-wires	9
Wattage	35.0 W
Lumen	1400 lm
Colour temperature	3000 Kelvin
Color	anthracite



Accessories

232195	MOUNTING POT , for H-POL pathway and floor stand, anthracite
--------	--

CRI	>80
Binning	6
LXXBXX data	70/50
Service life	30000 h
BIG WHITE Page	567

Notes
