

DISOS

outdoor floodlight, LED, 4000K, black, 70W

Powerful DISOS LED floodlight to light up areas and courtyards. With a tiltable installation bracket and protection class lp65, the floodlight is suitable for outdoor installation on the wall or on the floor. The electrical connection of the floodlight, which comes in cold-white, is done using the built-in driver and connection lead directly to the 230V mains supply. Various wall brackets are available for easy wall mounting. This luminaire contains built-in 68.5W LED lamps.

TECHNICAL DATA

Item no.:	232370		
Lamps included	0		
Number of different light outlets	1		
Primary nominal voltage	100-240V ~50/60Hz mA/V		
Secondary power / secondary voltage	80 mA/V		
Length	25.5 cm		
Width	12.0 cm		
Height	30.0 cm		
Net weight	3.72 kg		
Gross weight	4.485 kg		
IP Code	IP 65		
Safety class	I		
Impact resistance class	IK06		
Impact resistance	1 Joule		
Assembly	Surface		
Assembly details	Ground, Wall		
Wattage	73.0 W		
Lumen	8080 lm		
Colour temperature	4000 Kelvin		
Beam angle	110°		
Color	black		
CRI	>80		
	•		



Accessories

228730	CONNECTION BOX , 3-pin, IP68
234340	Wall bracket , for Outdoor Beam and MILOX floodlight, black, 50cm
234350	WALL BRACKET , for SPOODI 15/20/31, black, 80 cm

Binning	6
LXXBXX data	70/50
Service life	35000 h

Notes		