




SPOODI 31

outdoor spot, LED, 3000K, IP55, square, black, max. 55W

Powerful LED spot SPOODI 31 for illuminating areas and spaces. With a tiltable installation bracket and protection class IP55, the spot is suitable for outdoor installation on the wall or on the floor. By means of the incorporated driver and connection lead with mains plug, the spot supplied ready for direct connection to 230V mains supply.

TECHNICAL DATA

Item no.:	232840
Lamps included	0
Primary nominal voltage	230V ~50Hz mA/V
Vertical tilting range	180 °
Length	31.0 cm
Width	6.0 cm
Height	25.0 cm
Net weight	3.321 kg
Gross weight	3.71 kg
IP Code	IP 55
Safety class	I
Impact resistance class	IK04
Impact resistance	0,5 Joule
Assembly	Surface
Assembly details	Ceiling,Ground,Wall
Wattage	60.0 W
Lumen	5100 lm
Colour temperature	3000 Kelvin
Beam angle	100 °
Color	black
CRI	>80
Binning	6



Accessories

234340	Wall bracket , for Outdoor Beam and MILOX floodlight, black, 50cm
234350	WALL BRACKET , for SPOODI 15/20/31, black, 80 cm

LXXBXX data	70/50
Service life	30000 h
BIG WHITE Page	603

Notes
