



MYRALED WALL

outdoor wall and ceiling light, LED, 3000K, IP55, anthracite, 6.8W

The LED wall light of the NEW MYRA series is made from painted aluminium and equipped with a glass which covers the installed LEDs. The lamp heads can be rotated and swivelled. With protection class IP55, it is suitable for outdoor use. The electrical connection of the luminaire, which is available in different colour versions, is made directly to the 230V mains supply thanks to the built-in LED driver. MYRALED WALL includes other floor stands, display fittings and can therefore be used universally.

TECHNICAL DATA

Item no.:	233205
Lamps included	0
Primary nominal voltage	100-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500 mA/V
Vertical tilting range	45 °
Horizontal rotation range	340 °
Width	8.0 cm
Height	10.5 cm
Diameter	7.0 cm
Depth	15.0 cm
Net weight	0.66 kg
Gross weight	0.734 kg
IP Code	IP 55
Safety class	I
Assembly	Surface
Assembly details	Ceiling, Wall
Wattage	6.8 W
Lumen	350 lm
Colour temperature	3000 Kelvin
Beam angle	30 °
Color	anthracite
CRI	>80



Accessories

Binning	6
LXXBXX data	70/50
Service life	30000 h

233214	FRAME , for MYRA DISPLAY, MYRALED WALL, MYRA WALL and MYRA, silver-grey
--------	---

Notes
