



DASAR MINI 37

outdoor inground fitting, LED, 3000K, IP67, round, brushed stainless steel, 12-24V, 2W

The inground fitting and recessed wall light fitted with one power LED, DASAR MINI 37 can also be used for outdoor applications with its IP67 protection. The stainless steel luminaire is available with round or square cover. The electrical connection is made by the connection lead of a separately available 350mA or 24V LED power supply.

TECHNICAL DATA

Item no.:	233540
Lamps included	0
Primary nominal voltage	12-24V mA/V
Diameter	3.7 cm
Depth	6.7 cm
Installation diameter	3.0 cm
Installation depth	8.0 cm
Net weight	0.353 kg
Gross weight	0.423 kg
IP Code	IP 67
Safety class	III
Impact resistance class	IK08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground
Wattage	2.0 W
Lumen	120 lm
Colour temperature	3000 Kelvin
Beam angle	30 °
Color	stainless steel
CRI	>80
Binning	6

Accessories

470502	LED POWER SUPPLY , 12W, 24V
470507	LED POWER SUPPLY , 12W, 12V

LXXBXX data	70/50
Service life	25000 h
Mechanical loading	0,25 t
BIG WHITE Page	723

Notes
