


DASAR MINI 37

outdoor inground fitting, LED, 3000K, IP67, square, brushed stainless steel, 12-24V, 2W

The inground fitting and recessed wall light fitted with one power LED, DASAR MINI 37 can also be used for outdoor applications with its IP67 protection. The stainless steel luminaire is available with round or square cover. The electrical connection is made by the connection lead of a separately available 350mA or 24V LED power supply.



TECHNICAL DATA

Item no.:	233550		
Lamps included	0		
Primary nominal voltage	12-24V mA/V		
Length	3.7 cm		
Width	3.7 cm		
Depth	6.7 cm		
Installation diameter	3.0 cm		
Installation depth	8.0 cm		
Net weight	0.362 kg		
Gross weight	0.427 kg		
IP Code	IP 67		
Safety class	III		
Safety class Impact resistance class	III IK08		
Impact resistance class	IK08		
Impact resistance class Impact resistance	IK08 5 Joule		
Impact resistance class Impact resistance Assembly	IK08 5 Joule Recessed		
Impact resistance class Impact resistance Assembly Assembly details	IK08 5 Joule Recessed Ground		
Impact resistance class Impact resistance Assembly Assembly details Wattage	IK08 5 Joule Recessed Ground 2.0 W		
Impact resistance class Impact resistance Assembly Assembly details Wattage Lumen	IK08 5 Joule Recessed Ground 2.0 W 120 Im		
Impact resistance class Impact resistance Assembly Assembly details Wattage Lumen Colour temperature	IK08 5 Joule Recessed Ground 2.0 W 120 Im 3000 Kelvin		
Impact resistance class Impact resistance Assembly Assembly details Wattage Lumen Colour temperature Beam angle	IK08 5 Joule Recessed Ground 2.0 W 120 Im 3000 Kelvin 30 °		



Accessories

470502	LED POWER SUPPLY , 12W, 24V
470507	LED POWER SUPPLY, 12W, 12V

6
70/50
25000 h
0,25 t
723

Notes			