




DASAR PROJECTOR

outdoor floodlight, LED, 3000K, IP68, anodised aluminium, 12-24V, 7W

The surface-mounted DASAR PROJECTOR series lights are fitted with a 7W premium LED and available with a warm-white colour of light. The electrical connection is to a compatible 12V or 24V DC power supply. With IP68 protection class, the luminaire is suitable for outdoor use. The anodised aluminium DASAR PROJECTOR series includes a further stainless steel version, among other things. This luminaire has built-in LED lamps and can be used as a spike luminaire with an earth spike. The lamps in the luminaire cannot be replaced.



TECHNICAL DATA

Item no.:	233560
Primary nominal voltage	12-24V mA/V
Vertical tilting range	90 °
Length	7.2 cm
Width	10.0 cm
Height	10.8 cm
Net weight	0.66 kg
Gross weight	0.745 kg
IP Code	IP 68
Safety class	III
Assembly	Surface
Assembly details	Ceiling, Ceiling with Acc., Ground, Ground with Acc., Wall, Wall with Acc.
Wattage	7.0 W
Lumen	360 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	aluminium
CRI	>80
Binning	6
LXXBXX data	70/50
Service life	25000 h

Accessories

233580	EARTH SPIKE , for DASAR PROJECTOR, stainless steel 316
233582	INSTALLATION PLATE , for DASAR PROJECTOR outdoor floodlight, stainless steel 316
470502	LED POWER SUPPLY , 12W, 24V
470507	LED POWER SUPPLY , 12W, 12V
900011	PLASTIC EARTH SPIKE , black, length 17.5cm

Notes
