



## ADI

## outdoor recessed wall light, LED, 3000K, IP55, anthracite, 15,4W

The ADI recessed wall light is made of aluminium and is fitted with powerful premium LEDs. It has an indirect, glare-free light outlet which points downwards. The curved design was developed by the designer, David Morgen. Thanks to its IP55 protection class, the luminaire is suitable for outdoor use. The electrical connection to the luminaire can be made with 100-277V. For easy installation, we recommend the appropriate mounting pot as an accessory.

## **TECHNICAL DATA**

Lamps included0Primary nominal voltage100-277V ~50/60Hz mA/Secondary power / secondary voltage500 mA/V	V	
	V	
Secondary power / secondary voltage 500 mA/V		
Width 30.0 cm		
Height 13.0 cm		
Depth 11.1 cm		
Installation length 10.8 cm		
Installation width 25.0 cm		
Installation depth 8.8 cm		
Net weight 1.559 kg		
Gross weight 1.84 kg		
IP Code IP 55		
Safety class		
Impact resistance class IK02		
Impact resistance 0,200000000000001 J	0,2000000000000001 Joule	
Assembly Recessed	Recessed	
Assembly details Wall		
Wattage 18.0 W		
Lumen 870 lm		
Colour temperature 3000 Kelvin		
Color anthracite		



		CRI	>80
Accessories		Binning	5
		LXXBXX data	70/50
233639	MOUNTING POT , for ADI outdoor re- cessed wall light, black	Service life	25000 h
		BIG WHITE Page	700

Notes