



DASAR 100 PREMIUM

outdoor inground fitting, LED, 3000K, IP67, square, stainless steel, 24°, L/W/H 10.5/10.5/9.43 cm, 3.8W

The walk-on and scratch resistant high-voltage inground fitting DASAR 100 PREMIUM with its round stainless-steel bezel and glass cover is fitted with warm-white, high-performance power LEDs. With its IP67 protection class, the luminaire is suitable for outdoor use. The electrical connection is made directly to the 230V mains supply. In addition, the luminaire has high thermal, chemical, mechanical and optical resistance. There are other versions of the luminaire with different beam angles or, alternatively, with a stainless steel housing available. This luminaire contains built-in LED lamps.





TECHNICAL DATA

| Item no.: | 233702 | |
|-------------------------------------|------------------------|--|
| Lamps included | 0 | |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V | |
| Secondary power / secondary voltage | 400 mA/V | |
| Length | 10.5 cm | |
| Width | 10.5 cm | |
| Depth | 9.4 cm | |
| Installation diameter | 8.6 cm | |
| Installation depth | 13.4 cm | |
| Net weight | 1.127 kg | |
| Gross weight | 1.228 kg | |
| IP Code | IP 67 | |
| Safety class | 1 | |
| Impact resistance class | IK08 | |
| Impact resistance | 5 Joule | |
| Assembly | Recessed | |
| Assembly details | Ground | |
| Wattage | 5.5 W | |
| Lumen | 300 lm | |
| Colour temperature | 3000 Kelvin | |
| Beam angle | 24 ° | |
| Color | stainless steel | |
| | | |



| | | CRI | >80 |
|-------------|-------------------------------|-----------------------------|---------|
| Accessories | | Binning | 6 |
| | | LXXBXX data | 70/50 |
| 228726 | T-CONNECTIONBOX , black, IP68 | Service life | 30000 h |
| | | Maximum ambient temperature | 40 °C |
| | | Mechanical loading | 2 t |

Notes