

## **CEILING LIGHT 118**

outdoor wall and ceiling light, LED, 4000K, IP66, grey, L/W/H 118/14.5/11 cm, 6400lm, 48W

The functional wall and ceiling light has a diffuser which creates a pleasant light distribution. The luminaire was designed with powerful LEDs and is available in several lengths. The IP luminaire is fitted with a neutral white LED. Thanks to the built-in ballast, the luminaire ready for direct connection to the 230V mains supply.

## **TECHNICAL DATA**

| Item no.:                         | 234164                 |  |  |
|-----------------------------------|------------------------|--|--|
| Lamps included                    | 0                      |  |  |
| Number of different light outlets | 1                      |  |  |
| Primary nominal voltage           | 220-240V ~50/60Hz mA/V |  |  |
| Length                            | 117.5 cm               |  |  |
| Width                             | 14.5 cm                |  |  |
| Height                            | 11.0 cm                |  |  |
| Net weight                        | 2.583 kg               |  |  |
| Gross weight                      | 2.923 kg               |  |  |
| IP Code                           | IP 66                  |  |  |
| Safety class                      | 1                      |  |  |
| Impact resistance class           | IK10                   |  |  |
| Impact resistance                 | 30 Joule               |  |  |
| Assembly                          | Surface                |  |  |
| Assembly details                  | Ceiling,Wall           |  |  |
| Wattage                           | 48.0 W                 |  |  |
| Lumen                             | 5830 lm                |  |  |
| Colour temperature                | 4000 Kelvin            |  |  |
| Beam angle                        | 120 °                  |  |  |
| Color                             | grey                   |  |  |
| CRI                               | >80                    |  |  |
| Binning                           | 6                      |  |  |
|                                   | '                      |  |  |





| LXXBXX data         | 70/50   |
|---------------------|---------|
| Service life        | 50000 h |
| Ambient temperature | 45 °C   |

| Notes |  |  |  |
|-------|--|--|--|
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |