


LIGHT PIPE

pathway and floor stand, LED, 2700K, white, Ø/H
10/60 cm

In the LIGHT PIPE LED floor stand, the opal acrylic tube lighting surface is illuminated in warm-white by the LED module. With protection class IP55, it is suitable for outdoor use. For easy installation, an earth spike and an outdoor or indoor mounting plate are available as an option. This luminaire contains built-in dimmable LED lamps.



TECHNICAL DATA

Item no.:	234401
Lamps included	0
Primary nominal voltage	220-240V ~50/60Hz mA/V
Height	60.0 cm
Diameter	10.0 cm
Net weight	1.415 kg
Gross weight	1.649 kg
IP Code	IP 55
Safety class	I
Impact resistance class	IK02
Impact resistance	0,200000000000000001 Joule
Assembly	Surface
Assembly details	Ceiling,Ground
Wattage	11.0 W
Lumen	630 lm
Colour temperature	2700 Kelvin
Color	white
CRI	>80
Binning	6
LXXBXX data	70/50
Service life	20000 h
Minimum ambient temperature	-20 °C

Accessories

234430	EARTH SPIKE , for LIGHT PIPE path-way and floor stand, galvanised steel
234431	MOUNTING PLATE , outdoor, for LIGHT PIPE pathway and floor stand, white, with black cable
234441	MOUNTING PLATE , indoor, for LIGHT PIPE pathway and floor stand, white, with clear cable

Maximum ambient temperature	60 °C
BIG WHITE Page	28

Notes