



P-LIGHT

ceiling light, double-headed, LED, 6000K, oval, white, 6,5W

P-LIGHT suitable for use as emergency lighting for surface-mounted wall and ceiling lights. Can also be used as emergency indication luminaire with the optionally available pictograms. The safety lights are fitted with two built-in Ni-MH batteries with an automatic self-test and detection range of 30m. The emergency operating time of the luminaires is three hours. The luminaires can be operated permanently switched on / stand-by operation. The electrical connection is directly to the 230V supply. Other variants of the P-LIGHT series are available.

TECHNICAL DATA

Item no.:	240005
Lamps included	0
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Length	18.5 cm
Width	10.4 cm
Height	5.5 cm
Net weight	0.491 kg
Gross weight	0.571 kg
IP Code	IP 20
Safety class	II
Assembly	Surface
Assembly details	Ceiling, Wall
Wattage	6.5 W
Lumen	220 lm
Colour temperature	6000 Kelvin
Beam angle	30 °
Color	white
CRI	>75
LXXBXX data	70/50
Service life	25000 h



Accessories

240023	RECHARGEABLE BATTERY , for P-LIGHT, 3.6V, 1500mA
--------	--

Notes
