

## VALETO LED

## QPAR51, dimmable, 2700K, 5,3W

Dimmable SMART LED QPAR51 as an ideal replacement for HV halogen lamps with GU10 socket. This LED lamp is also ideal for use in general lighting applications. LED floodlights create a warm light beam, comparable with halogen lamps, and are ideal for use as accent lighting. Dimmable lamp for our SLV VALETO® SMART HOME SYSTEM and can be controlled using the Remote Control CCT/DIM. LED spots are compatible with most existing luminaires with a GU10 socket and have been developed specially as replacements for halogen lamps. LED lamps provide increased energy savings and much lower maintenance costs. The product has an energy efficiency index of A+.

## **TECHNICAL DATA**

| Item no.:                   | 420060              |  |
|-----------------------------|---------------------|--|
| Socket                      | GU10                |  |
| Lamp type                   | LED GU10 51mm       |  |
| Nominal voltage             | 220-240V ~50/60Hz V |  |
| Height                      | 5.5 cm              |  |
| Diameter                    | 5.0 cm              |  |
| Net weight                  | 0.056 kg            |  |
| Gross weight                | 0.068 kg            |  |
| IP Code                     | IP 20               |  |
| Dimmable                    | Ja                  |  |
| Energy efficiency index     | A+                  |  |
| Weighted energy consumption | 6 kWh/1000h         |  |
| Electrical power factor     | 0,637               |  |
| Wattage                     | 5.3 W               |  |
| Lumen                       | 385 lm              |  |
| Lumen                       | 70 lm               |  |
| Colour temperature          | 3000 Kelvin         |  |
| Beam angle                  | 36 °                |  |
| Color                       | white               |  |
| CRI                         | >80                 |  |
| Binning                     | 6                   |  |
| Service life                | 25000 h             |  |
|                             |                     |  |



|             |  | Switching cycles     | 25000 |
|-------------|--|----------------------|-------|
| Accessories |  | Start-up time        | 0 s   |
|             |  | Ambient temperature  | 40 °C |
|             | REMOTE CONTROL RGBW, remote<br>control for SLV VALETO SMART SYS- | Lamp mercury content | 0 mg  |
|             | TEM  |                      |       |

Notes