

## PROFILE-STRIP STAND 180

## 24V 10mm x 3 m, 3000K, 1600lm/m

Flexible LED strip, 3 m long, to connect to a 24V DC voltage power supply. The rear side is fitted with adhesive tape to make for simple installation. The strips come in several colours of light. To obtain constant light output over long lengths, the strips should be powered on both sides. For lengths in excess of 3 m, a new feed-in must be made.

## **TECHNICAL DATA**

Item no.:	552783
Nominal voltage	24V DC V
Length	300.0 cm
Width	1.0 cm
Height	0.2 cm
Net weight	0.051 kg
Gross weight	0.1 kg
IP Code	IP 20
Safety class	III
Assembly	Surface
Assembly details	Ceiling,Wall
Wattage	50.0 W
Lumen	4800 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
CRI	>80
Binning	3
LED distance	0,55 cm
Service life	25000 h
Switching cycles	12500
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C

									4				4			4		4		4	ч	4	4	4	4	ч	4	4	4								
	٠,	ı,		ı		a,	J.	J	J	J.	J	a,	J	J	J	J	J,	a,	a,	J.	ä																
ı,	. د	ı	ı	1	J	J.	1	J	1	ä	J	ä	ı	J	J	J	ä	J	ä		ä			J		4		J	J	4	J	J.	a,	1	ı	ı	J
							ы			ы		а		а	a.	а	a.	a.	a.	J.	J.	J.	а	а	л	J.	1	a.	а	а							



BIG WHITE Page	782
----------------	-----

Notes			