

DELF D

light bar, 30 LED, 3000K, L/W 50.5/1.5 cm, 24V

SLV DELF D filigree, modular plug & play light bar system made of anodised aluminium and plastic. Feed-in cables, flexible connectors and mounting clips are available as accessories. Thanks to the built-in plug contacts, the profiles can be connected directly to each other. The electrical connection of the profiles, which come in several lengths, is done to a separately available 24V DC power supply. This luminaire includes built-in LED lamps.

TECHNICAL DATA

| Item no.: | 631505 | |
|-----------------------------|---------------------|--|
| Lamps included | 0 | |
| Primary nominal voltage | 24V mA/V | |
| Length | 50.5 cm | |
| Width | 1.5 cm | |
| Height | 1.4 cm | |
| Net weight | 0.082 kg | |
| Gross weight | 0.11 kg | |
| IP Code | IP 20 | |
| Safety class | III | |
| Assembly | Surface | |
| Assembly details | Ceiling,Ground,Wall | |
| Wattage | 6.3 W | |
| Lumen | 500 lm | |
| Colour temperature | 3000 Kelvin | |
| Beam angle | 110° | |
| Color | aluminium | |
| CRI | >80 | |
| Binning | 3 | |
| LXXBXX data | 70/50 | |
| Service life | 30000 h | |
| Minimum ambient temperature | -20 °C | |
| | | |





Accessories

| 470502 | LED POWER SUPPLY , 12W, 24V |
|--------|------------------------------------------------------|
| 470547 | TCI LED POWER SUPPLY , 20W, 24V, incl. strain relief |

| Maximum ambient temperature | 40 °C |
|-----------------------------|-------|
| BIG WHITE Page | 813 |

| Notes | | |
|-------|--|--|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |