



DELFD

light bars, 30 LED, RGB, L/W 50.5/1.5 cm, 24V

SLV DELFD RGB filigree, modular plug & play light bar system made of anodised aluminium and plastic. Feed-in cables, flexible connectors and mounting clips are available as accessories. Thanks to the built-in plug contacts, the profiles can be connected directly to each other. The electrical connection of the profiles, which come in several lengths, is done to a separately available 24V DC power supply. A separate controller is needed to control the RGB effects. This luminaire includes built-in LED lamps.

TECHNICAL DATA

Item no.:	631535
Lamps included	0
Primary nominal voltage	24V mA/V
Length	50.5 cm
Width	1.5 cm
Height	1.4 cm
Net weight	0.086 kg
Gross weight	0.107 kg
IP Code	IP 20
Safety class	III
Assembly	Surface
Assembly details	Ceiling, Ground, Wall
Wattage	12.0 W
Beam angle	110 °
Color	aluminium
CRI	>80
LXXBXX data	70/50
Service life	30000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C

Accessories

470502	LED POWER SUPPLY , 12W, 24V
470547	TCI LED POWER SUPPLY , 20W, 24V, incl. strain relief
631550	FEED-IN , for DELF D light bars RGB, single colour, 1.5 m, max. 50W
631551	CONNECTOR , for DELF D light bars RGB, single colour, 12 cm, max.50W

Notes
