



DELFD

light bars, 60 LED, RGB, L/W 100.5/1.5 cm, 24V

SLV DELFD RGB filigree, modular plug & play light bar system made of anodised aluminium and plastic. Feed-in cables, flexible connectors and mounting clips are available as accessories. Thanks to the built-in plug contacts, the profiles can be connected directly to each other. The electrical connection of the profiles, which come in several lengths, is done to a separately available 24V DC power supply. A separate controller is needed to control the RGB effects. This luminaire includes built-in LED lamps.

TECHNICAL DATA

| | |
|-----------------------------|-----------|
| Item no.: | 631540 |
| Lamps included | 0 |
| Primary nominal voltage | 24V mA/V |
| Length | 100.5 cm |
| Width | 1.5 cm |
| Height | 1.4 cm |
| Net weight | 0.155 kg |
| Gross weight | 0.194 kg |
| IP Code | IP 20 |
| Safety class | III |
| Wattage | 12.1 W |
| Beam angle | 110 ° |
| Color | aluminium |
| CRI | >80 |
| LXXBXX data | 70/50 |
| Service life | 30000 h |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |

Accessories

| | |
|--------|---|
| 470502 | LED POWER SUPPLY , 12W, 24V |
| 470547 | TCI LED POWER SUPPLY , 20W, 24V, incl. strain relief |
| 631550 | FEED-IN , for DELF D light bars RGB, single colour, 1.5 m, max. 50W |
| 631551 | CONNECTOR , for DELF D light bars RGB, single colour, 12 cm, max.50W |

Notes
